



159.00 EUR  
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- Intel Atom Processor D510 / D525 + NM10 Express Chipset
- Support INTEL® Atom Processor D510 / D525
- Support Single Channel DDR 800
- Supports 10M/100M LAN
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support Watch dog Technology
- Support O.V.P Function
- Support CPU Smart FAN
- Mini-ITX Form Factor(170mm x 170mm)

• **CPU**

• **Chipset**

• **Memory**

• **Expansion Slots**

• **Storage**

• **Audio**

• **Ethernet LAN**

• **USB**

- INTEL ® Atom Processor D510 (45nm,1.66GHz,1024MB L2 Cache)
- INTEL ® Atom Processor D525 (45nm,1.80GHz,1024MB L2 Cache)
- INTEL® Atom Processor D510 / D525 + NM10 Express Chipset
- 2 \* 240-pin DIMM Sockets for un-buffered Single Channel DDR2 800/667 SDRAM up to 4 GB
- 1 \* PCI-E x16 slot (by 4)
- 2 \* Serial ATA2 3Gb/s connectors
- 1 \* Floppy connector
- Realtek ALC662 6-Channel HD Audio CODEC
- INTEL 82552V 10M/100M LAN
- Embedded 8 \* USB 2.0/1.1

- **Special Features**

- **Rear Panel I/O**

- **Internal I/O**

- **BIOS**

- **Functional**

- **Packing**

- **Certificate**

- **Temperature**

- **Form Factor**

**Product Accessories**

- Manual
- CD
- 1x SATA cable
- I/O shield

- Intel Atom Processor D525/D510/D410 Support DC FAN
- Support CPU Smart Fan Support Watch Dog Technology
- 4 \* USB 2.0/1.1 ports 1 \* COM port 1 \* Parallel port
- 1 \* PS/2 Mouse & 1 \* Keyboard connector 1 \* RJ-45 port
- 3 \* Audio I/O ports ( Line-in, mic and line-out ) 1 \* VGA port
- 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports 3 \* NB / Chassis Fan connectors;
- 1 \* 20-pin ATX Power connector 1 \* GPIO header
- 1 \* 18-bit Single Channel LVDS header/1\* CD IN/1\*LPC
- 1 \* AUDIO header 1\* RS232/RS422/RS485 connectors
- AMI 8MB SPI Flash ROM
- ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
- Color Box Dimension 200(W) x 200(D) x 70(H)mm
- CE, FCC, RoHS
- Operating within 0~50 centigrade (**Suggest to use system FAN**)
- Storage within -20-85 centigrade
- Mini ITX Form Factor(17cmx17cm)