

49.95 EUR
incl. 19% VAT, plus shipping

- Intel Celeron 1037U !
- Dual Gigabit LAN !
- WinXP, Win7, Win 8 !

From demo machines. Remnant with I/O shield, 1x SATA cable, 2GB RAM. 2 years warranty.

- GIGABYTE Dual UEFI BIOS
- All new design of Ultra Durable 4 classic
- Industry's Leading All Solid Capacitor Design
- Dual LAN for networking flexibility
- HDMI interface for smoother HD video playback
- GIGABYTE On/Off Charge™ for USB devices

CPU	1. Built in with an Intel® Dual-core Celeron® 1037U processor (1.8 GHz) * Do not disassemble the onboard CPU/chipset and the heatsinks by yourself to avoid damage to these components. 2. 2 MB L3 cache
Chipset	1. Intel® NM70 Chipset
Memory	1. 2 x DDR3 DIMM sockets supporting up to 16 GB of system memory * Due to a Windows 32-bit operating system limitation, when more than 4 GB of physical memory is installed, the actual memory size displayed will be less than the size of the physical memory installed. 2. Dual channel memory architecture 3. Support for DDR3 1600/1333 MHz memory modules (Please refer "Memory Support List" for more information.)
Onboard Graphics	Integrated Graphics Processor: 1. 1 x D-Sub port 2. 1 x HDMI port, supporting a maximum resolution of 1920x1200 * Support for HDMI 1.4 version. 3. Maximum shared memory of 1 GB

Audio	1. Realtek® ALC887 codec 2. High Definition Audio 3. 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you have to use an HD front panel audio module and enable the multi-channel audio feature through the audio driver.
LAN	1. 2 x Realtek® GbE LAN chips (10/100/1000 Mbit) * Teaming is not supported.
Expansion Slots	1. 1 x PCI slot
Storage Interface	Chipset: 1. 1 x SATA 6Gb/s connector (SATA3 0) 2. 2 x SATA 3Gb/s connectors (SATA2 1~2) 3. 1 x eSATA 3Gb/s connector on the back panel
USB	Chipset: 1. 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)
Internal I/O Connectors	1. 1 x 24-pin ATX main power connector 2. 1 x 4-pin ATX 12V power connector 3. 1 x SATA 6Gb/s connector 4. 2 x SATA 3Gb/s connectors 5. 1 x CPU fan header 6. 1 x system fan header 7. 1 x front panel header 8. 1 x front panel audio header 9. 2 x USB 2.0/1.1 headers 10. 1 x parallel port header 11. 1 x serial port header 12. 1 x Clear CMOS jumper 13. 1 x chassis intrusion header

Back Panel Connectors	1. 1 x PS/2 keyboard port 2. 1 x PS/2 mouse port 3. 1 x D-Sub port 4. 1 x serial port 5. 1 x HDMI port 6. 4 x USB 2.0/1.1 ports 7. 1 x eSATA 3Gb/s connector 8. 2 x RJ-45 ports 9. 3 x audio jacks (Line In, Line Out, Mic In)
I/O Controller	1. iTE® I/O Controller Chip
H/W Monitoring	1. System voltage detection 2. CPU/System temperature detection 3. CPU/System fan speed detection * Whether the fan speed detect function is supported will depend on the cooler you install. 4. System fan speed control * Whether the fan speed control function is supported will depend on the cooler you install.
BIOS	1. 2 x 32 Mbit flash 2. Use of licensed AMI UEFI BIOS 3. Support for DualBIOS™ 4. PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features	1. Support for @BIOS 2. Support for Q-Flash 3. Support for Xpress Install 4. Support for EasyTune * Available functions in EasyTune may differ by motherboard model. 5. Support for Smart Recovery 2 6. Support for Auto Green 7. Support for ON/OFF Charge

Bundle Software	1. Norton® Internet Security (OEM version) 2. Intel® Smart Connect Technology
Operating System	1. Support for Windows 8.1/8/7/XP
Form Factor	1. Mini-ITX Form Factor; 17.0cm x 17.0cm
Remark	1. Due to different Linux support condition provided by chipset vendors, please download Linux driver from chipset vendors' website or 3rd party website. 2. Most hardware/software vendors may no longer offer drivers to support Win9X/ME/2000/XP SP1/SP2. If drivers are available from the vendors, we will update them on the GIGABYTE website.