

198.95 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications](#) | [BIOS](#)

- Support Intel 6th generation Intel Core Processor
- LGA1151 SKL-S CPU compatible (up to 65W)
- Dual channel DDR4 with two connectors (up to 16GB)
- High speed Gigabit Ethernet connection
- Two PCI Express Mini Card connector for expansion
- Features 2 SATA3 (6Gbps)
- Four Hi-Speed external USB3.0 ports support
- HD-out & VGA display connectivity
- Embedded LVDS/ connectivity

Item

Form Factor

Spec

Thin Mini-iTX (170mm x 170mm), 6 layers

	CPU Type : Intel Skylake-S Desktop platform		
Processor	CPU Core : Dual Core / Quad Core		
	Socket : Socket LGA1151		
	TDP : Support up to 65W CPU types		
Chipset	Chipset Series : Intel® H110 Chipset		
	Integrated GFX by CPU		
	Graphic Core : Gen9		
Graphics	Graphic Memory : Shared Memory		
	3D : DX12, OpenGL 4.3/4.4		
	Computing : OpenCL 2.0		
Memory	Memory Socket: 260-pin So-DIMM socket	2	
	Memory Type: DDR4 @ 1.2V, 2133MHz (Unbuffered Non-ECC)		
	Memory Channel: Dual Channel		
	Memory Capacity : Support total up to 32GB (16GB each by 2 SO-DIMM)		
	ECC Support : No		
SIO Controller	IT8519E		
LAN Controller	Realtek RTL8111G, 10/100/1000 support		
Audio Controller	Codec: HD audio codec, Realtek ALC662 AMP for internal speaker		
Display Controller	Parade DP701		
Expansion slot	PCI-E Mini Card (Half) x 1, Signal: PCIe, USB2.0 for WiFi/BT module		
	PCI-E Mini Card (Full) x 1, Signal: PCIe, SATA3.0 for mSATA or TV card		
	HD-out	1	
External I/O	VGA out	1	
	USB3.0	4	
	RJ-45 (with integrated status LEDs)	1	
	Line-out	1	
	Mic-in	1	
	DC-in Jack (19V DC; 5mm/ ID, 7.5mm/ OD)	1	
	LVDS connector	1	
	Converter BD header	1	
	Light sensor header	1	
	USB 2.0 header	5	
	SATA Connector	2	
	Internal I/O	SATA Power	1
		CPU Fan header	1
Speaker header		1	
Side SW/LED header		1	
DMIC header		1	
19V 2 pin power header (Option#1)			
12V 4 pin power header (Option#2)			
Power	Option#1: 19V DC-in, 19V 2pin power header		
	Option#2: 12V DC-in, 12V 4pin power header		
BIOS	AMI BIOS		
Compliance	CE		
	FCC		