



999.00 EUR
incl. 19% VAT, plus [shipping](#)

- Fanless Black Aluminum Enclosure
- Support Intel LGA1151 Socket 6th & 7th generation Pentium, Core i3, i5, i7 Processors, Up to 35W
- Support DDR4-2133 SODIMM up to 32GB
- Support 3 * HDMI
- Support 2 * 2.5" SATA HDD
- Support Onboard TPM IC
- Watchdog Timer, 120W 19V AC Adapter

MB Model	- JNF793-Q170 Series/ MINI-ITX
Part No	- HBFFF793-Q170-B (non-WIFI) / HBFFF793W-Q170-B (WIFI) - HBFFF793-Q170-T1 (TPM1.2, non-WIFI) / HBFFF793W-Q170-T1 (TPM1.2, WIFI) - HBFFF793-Q170-T2 (TPM2.0, non-WIFI) / HBFFF793W-Q170-T2 (TPM2.0, WIFI)
BIOS	- AMI 16MB SMT Flash ROM
CPU/Chipset	- Intel® LGA 1151 Socket 6th & 7th generation Core i7 / i5 / i3 / Pentium CPU (35W) - Intel® Q170 chipset Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.
Memory	- 2 * SO-DIMM slots / dual channel DDR4-2133 up to 32GB total
Storage	- 2 * 2.5" SATA3 6Gb/s internal drive bay - 1 * Full-size mSATA slot
Network	- 2 * Intel Gigabit LAN (i219LM,i211AT)
Expansion	- 1 * Half-size Mini-PCI Express shared slot (for WIFI module)
Rear Panel I/O	- 4 * USB 3.0 ports - 3 * HDMI - 2 * RJ45 - Line-in, Line-out, MIC - 2 * COM (RS232/422/485), 4 * COM (RS232/optional) - 1 * DC-In jack
Front Panel I/O	- 1 * Power button, 1 * HDD LED - 2 * USB 2.0 ports - 2 * 2.5" HDD Tray (Easy to replace the hard disk, does not support hot swap)

Power Source	- FSP AC to DC Adapter 19VDC-6.3A 120W
Compliance	- CE, FCC, LVDS, RoHS, ErP Ready
Temperature	- Operating Temperature: 0 ~ 40° C - Storage Temperature: -20 ~ 75° C
Dimensions	- 290 (W) x 207 (D) x 65 (H) mm
Packing	- Net Weight: 3.8KG - Gross Weight: 4.8KG
OS Support	- Windows 7, Windows 8.1, Windows 10, Linux
Warranty	- 2 Year limited warranty