



489.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake SoC Processor
- 1 * DDR3L SODIMM Up to 8GB
- 4 * COM, 4 * USB3.0, 1 * HDMI, 1 * DP, 1 * RJ45, 1 * MIC, 1 * Line-in, 1 * Line-out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

| | |
|-----------------|---|
| MB Model | – JNF694L-3350 / Mini ITX – JNF694L-4200 / Mini ITX |
| Part No. | – HBJC143F694-335B (non-WIFI) / HBJC143F694W-335B (WIFI) – HBJC143F694-420B (non-WIFI) / HBJC143F694W-420B (WIFI) |
| BIOS | – AMI Flash ROM |
| CPU/Chipset | – INTEL® Apollo Lake SoC Processor |
| Memory | – 1 * DDR3L-1866 MHz up to 8 GB |
| Storage | – 1 * 2.5" SATA 6Gb/s_ internal drive bay – 1 * M.2_SSD (M key-2242/2260) |
| Network | – 1 * Realtek® 8111H Gigabit LAN – 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model / Optional) |
| Rear Panel I/O | – 4 * USB 3.0 – 1 * HDMI 1.4 (Max Resolution : 3840x2160@24Hz) – 1 * DP (Max Resolution : 4096x2160@60Hz) – 1 * RJ45 – 1 * MIC, 1 * Line-in , 1 * Line-out (Realtek ALC662) – 4 * RS232 – 1 * AC-in CON |
| Front Panel I/O | – 1 * Power button, 1 * Reset button – 1 * Power LED, 1 * HDD LED – 2 * USB 2.0 |
| Power Source | – 1U 200W FLEX POWER – AC 90~240V input |
| Compliance | – CE, FCC, RoHS |
| Temperature | – Operating Temperature: 0 ~ 50° C – Storage Temperature: -10 ~ 70° C |
| Dimensions | – 330 (W) x 192 (D) x 44 (H) mm |
| Packing | – Net Weight: 3.5KG – Gross Weight: 4.5KG – Color Box dimension: 406 (W) * 359 (D) * 148 (H) mm |
| OS Support | – Windows 10 64bit, latest Linux kernel |

Warranty

- 2 Year limited warranty