



79.95 EUR  
incl. 19% VAT, plus [shipping](#)



- Applied Solid Capacitor for CPU VRM to ensure a longer lifespan for system
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- Dual Display design for multiple output support
- Integrated Printer (LPT) port / header to expand functionality
- Microsoft Windows 8 Certified
- Intel® VRD 12 Ready
- Supports DirectX® 11 to enhance graphical performance
- Supports HDMI 1.4a Technology ( resolution up to 1920X1200 ) and HDCP function
- Free Bundle: CyberLink Media Suite

Supports Intel® CNVi

#### **CPU**

Onboard Intel® Bay Trail  
processors  
On-Board CPU Intel® Bay  
Trail J1900 processor  
VRD 12.0  
Solid Capacitor for CPU  
side  
Supports Intel®  
Hyper-Threading  
Technology

<b>GRAPHICS</b>	Supports DirectX® 11 Supports Full HD 1080P Blu-ray / HD-DVD Playback Single-channel DDR3
<b>MEMORY</b>	Memory architecture 1 X DDR3 SO-DIMM socket Support up to 8 GB
<b>EXPANSION SLOT</b>	1 X PCI Express X 1 Gen 2.0slot(s) 1 X Mini PCI Express X1 slot(s) for Wi-Fi /Bluetooth modules
<b>Storage</b>	2 X Serial ATAIII 3Gb/s
<b>Audio</b>	6-Channel HD audio CODEC Realtek ALC662 Realtek ALC662 6-channel High Definition audio CODEC Meets performance requirements for Microsoft WLP 3.08 Vista premium and mobile PCs Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution Emulation of 26 sound environments to enhance gaming experience Voice Cancellation and Key Shifting in Karaoke mode Compatible with Direct Sound 3D™, A3D™, I3DL2
<b>LAN</b>	Realtek RTL8111G Gigabit Fast Ethernet Controller
<b>USB</b>	1 X USB3.1 Gen1 port(s) up to 5Gb/s 6 X USB2.0 port(s) Up to 480 Mb/s ( Back Panel 4 port(s), Onboard 2 port(s)) 1 X PS/2 Keyboard & PS/2 mouse connectors 1 X Audio port (Line Out/Line In/Mic In)
<b>REAR PANEL I/O</b>	1 X RJ-45 port 1 X HDMI port(s) 1 X D-Sub (VGA) port(s) 1 X USB3.1 Gen1 port(s) 4 X USB2.0 port(s)

	1 X 4-pin CPU_FAN connector with smart fan
	1 X 4-pin SYS_FAN connector with smart fan
	1 X Front Panel MIC/Speaker out header
	1 X Front Panel switch/LED header
<b>CONNECTORS &amp; HEADERS</b>	1 X USB 2.0 header (Support additional 2 USB ports)
	2 X SATA II 3Gb/s connector(s)
	1 X CLR_CMOS header
	2 X Serial port header (COM)
	1 X Parallel port header (LPT)
	1 X LVDS connector (optional)
	AMI BIOS with 8 MB SPI Flash ROM
	Supports ACPI 5.0 & DMI
<b>SYSTEM BIOS</b>	Dual Display Plug and Play, STR (S3) / STD (S4) , Hardware monitor, Multi Boot
	Multi-Language BIOS
	Audio, LAN, can be disabled in BIOS
	Dual-Monitor function
<b>FORM FACTOR</b>	Mini ITX Form Factor 170*170
	Windows 7 64-bit
<b>OS Support</b>	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 64-bit
	Windows 10 32-bit
<b>Certifications</b>	CE/FCC Certification
	ErP/EuP Certification
	WHQL Certification
	WHCK Certification