

698.00 EUR

incl. 19% VAT, plus [shipping](#)



- Intel Comet Lake-S !
- Q470 Chipset !
- 19" Enclosure !

Support:  [Datasheet](#)

- Intel® 10th LGA1200 Socket Comet Lake-S Processor (Max. 65W TDP)
- Support 2* DDR4 2666/2400MHz SO-DIMM up to 32 GB
- 6* USB3.1, 2* USB2.0, 2* COM, 2* HDMI, 1* DP, 2* RJ45, 1* MIC, 1* Line out, 1* LineIn
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 250W FLEX Power

Dimensions	– 330 (W) x 192 (D) x 44 (H) mm		
MB model	– MI92-10 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm)		
Part No	Non-Wifi	Wifi	
	– HBJC150I92-Q470-B	– HBJC150I92I-Q470-B	
CPU/Chipset	– Intel® 10th LGA 1200 Socket Core i7/i5/i3/Pentium/Celeron Processor (Max. 65W TDP) – Q470 chipset		
BIOS	– AMI Flash ROM		
Memory	– 2* Dual CH non-ECC DDR4 2666/2400MHz SDRAM SO-DIMM up to 32GB		
Network	– 1 * Intel i219LM – 1 * Intel i211AT GbE		
Storage	– 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay – 1 * M.2_SSD (M key-2242/2280) support NVMe		
Expansion	– 1* M.2 E-key 2230 (PCIex1/USB2.0) support CNVi – Support onboard TPM2.0 (MI92-12) / optional		
Rear I/O Port	– 4 * USB3.1 (Gen. 2) – 2 * USB3.1 (Gen. 1) – 2 * HDMI 1.4 (Max Resolution: 4096x2160@30Hz) – 1 * DP (Max Resolution: 4096x2304@60Hz) – 2 * RJ45 (1 * Intel i219LM, 1 * Intel i211AT GbE) – 1 * MIC, 1 * Line in, 1 * Line out – 2 * COM (COM 1/2 support RS232/422/485) – AC-in CON		
Front I/O Port	– 1 * Power button, 1 * Reset button – 1 * Power LED, 1 * HDD LED – 2 * USB2.0		

Power Source	<ul style="list-style-type: none">- 1U 250W FLEX POWER- AC 90~240V input
Certification	<ul style="list-style-type: none">- CE, FCC, LVD, RoHS
Environment	<ul style="list-style-type: none">- Operating Temperature : 0°C~50°C- Storage Temperature : -10°C~70°C- Humidity: 10% ~ 90% RH @40°C (non-condensing)
Packing	<ul style="list-style-type: none">- Net Weight■3.5 KG- Gross Weight■4.5 KG- Color Box Dimension■560(W) x 400(D) x 140(H) mm