

819.00 EUR

incl. 19% VAT, plus [shipping](#)

- BayTrail-D J1900 !
- 4GB RAM !
- IP65 !
- 9-28V DC !



- 13.4" 220 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Intel® Bay Trail-D J1900 2.0GHz/QC processor
- Onboard DDR3L 1333MHz DRAM 4GB
- 2* GbE, 2* RS232/422/485), 2* RS232, 2* USB3.0, 2* USB2.0, 1* VGA
- 1* Mini PCIe, 1* M.2 M-key (2242/2260/2280, SATA interface)
- 9~28V DC-in
- Front bezel meets IP65-rated protection

Display	– IP65, NEMA 4 rugged protection, Full planar metal border – 13.4" With LED Backlight – 220 nits Brightness (cd/m²) – 262K display color – 1366 x 768 @ 60Hz resolution – 90°/65° viewing angle (H/V) – 0.17925 x 0.17925 mm pixel pitch – 16:9 aspect ratio – 500:1 contrast ratio – 11ms response time
Touch Screen	– Projected capacitive type – 340.00 x 200.00mm ±0.3mm active range – Transparency ■ 85% – Surface Hardness ■ 6H (JIS-5400) – Glass haze value ■ 3%
Case	– Aluminum panel – Iron case – Silver + Black color – Spray paint coating requirement
Main System	– Intel® Bay Trail-D J1900 2.0GHz/QC processor – Onboard DDR3L 1333MHz DRAM 4GB – 64MB SPI Flash ROM BIOS – Watchdog Timer: 256 levels, 0~255 sec. – OS Support: Windows 7 / 8.1 / 10 / Linux (Option)
Expansion	– 1* Mini PCIe for WIFI or 3G/4G
Storage	– 1* SATA – 1* M.2 M-key (2242/2260/2280, SATA Interface)
I/O Connector	– 2* USB3.0 – 2* USB2.0 – 2* RS232/422/485 – 2* RS232 – 1* VGA – 2* RJ45 (Intel I211AT GbE) – 1* Lockable 9~28V DC jack – 1* Power button
Power Input	– 9~28V DC-in – AC version: 100~240V AC-DC 60W power adapter or – DC version: 12VDC with over current protection fuse
Power Consumption	– 20W
Dimensions	– 347.42 * 228.00 * 56.60mm
Compliance	– CE, FCC, IP65 (Front)
Safety	– Shock: 15G, 11ms duration – Vibration: 5~500Hz/1 Grms
Temperature	– Operating: : -10°C ~ 60°C (with W.T. DRAM/HDD in airflow condition) – Operating: : -10°C ~ 60°C (with W.T. DRAM/HDD) – Storage: -20°C ~ 85°C